

Micom RM125 z

The best equipment for your dispatch center

Rack Mount - 125 Watt HF-SSB Transceiver 1.6 - 30 MHz



Dispatch Center AVL (GPS) with 1 Ch. Data , with 1 Ch. Audio & 1 Ch. Emmergency

The Micom RM125z is specifically designed to provide very long-range radio communications for fixed or mobile base-stations. Complete with a 125 W amplifier in a 19" rack mount configuration, the Micom RM125 features a detachable control head & extension cable in option. A 110/220 VAC power supply with charging battery backup (battery not include) cooling fans and a multiple accessory interface very useful for long & short range communications.

Meeting the world's strictest standards for radio equipment communication dependability, including MIL-STD-810, ALE per MIL-STD- 188-141B and FED-STD-1045, the Micom RM125 is the ideal solution for organizations whose operations require very reliable long-range radio communications for mission command and control.

Micom RM125 z

Rack Mount - 125 Watt HF-SSB Transceiver 1.6 - 30 MHz

Fast and simple link establishment

- Automatic Link Establishment per MIL-STD-1045 & MIL-STD-188-141 standards
- ISB ready (Independent Side Band)
- Full interoperability with other manufacturers' radios complying with the same ALE standards

Voice that's loud & clear

- Built-in voice quality system utilizes proprietary algorithms to filter out background noises, giving users exceptional communication clarity
- Selectable bandwidth allows fine tuning for optimal voice and data communications
- Voice-activated digital squelch

User-friendliness

- New control head features a large LCD, full dot matrix digital display and an enhanced keyboard for programming and set-up
- Radio operation can be executed using any standard USB keyboard
- Multiple language display available
- Transceiver can be controlled using PC and programming application
- Remote control configuration allows the transceiver to be operated from a remote location using optional 2 wire remote control head

Years of trouble-free, most advanced communications

- Upgrading to future technologies is easily done by installing new software into the transceiver's DSP unit
- Easily replaceable digital components ensure cost-effective active Maintenance
- Very high MTBF, as with all Micom radios
- Unique Built-In self-test system provides exceptional Dependability

Comprehensive communication and networking services

- Office-quality communication services integrating fax, e-mail and data transmission and reception
- MultiNet enabling integration of different HF radio networks into one seamless network, allowing excellent coordination between different operational nets.
- AMD (automatic Message Display) for free and pre-set text Messages.

A proven family of radio products

- The Micom RM125sz is member of the Micom transceiver family fixed and mobile stations—covering the long-range wireless communication needs of thousands of organizations worldwide

Major accessories

- Phone patch
- Antenna system
- ATUs
- Pre post selector (PPS)
- HF modems
- micomLink (Turbo X4 up to for radios dispatch)
- Antennas and grounding kit
- Secure voice and data

Model: M91AMN0KV5K & G638

Frequency range: 1.6–30 MHz

Number of channels: 200

Transmission: 125 W PEP average

Reception: 100 KHz–30 MHz Rx

Operating voltage: AC 110–220 V 47–65 Hz

DC 13.8 + 20%

Audio bandwidth: 350 to 2700 Hz

Data: 300 to 3000 Hz

Frequency stability: 0.6 PPM (0.1 PPM optional)

Frequency resolution: 10 Hz

Operating temperature range:

-30 °C to +60°C / -22°F to +140°F

Humidity: 95% @ 50 °C / 122°F

Sensitivity (SINAD): SSB: 0.3 µV for 10 dB SINAD

Dimensions

Height: 200 mm / 8 inch

Width: 485 mm / 19 inch

Depth: 510 mm / 20 inch

Weight: 16 Kg / 35.5 Lbs

Options:

- USB com port for external keyboard
- PC control and programming package
- PPS interface (internal/external pre-post selector)
- Interface for secure voice device VP116
- 2 wire remote control panel